

HST HARRI

FAST CREW SUPPLIER 2710

FAST TWIN AXE CREW SUPPLY VESSEL



GENERAL

| | |
|-----------------|--|
| Hull materials | Aluminium |
| Superstructure | Aluminium |
| Basic functions | Crew and cargo duties |
| Classification | Bureau Veritas Hull • MACH Light Ship / Fast Utility Vessel Sea Area 3 |
| Flag | MCA HS-OSC code |

DIMENSIONS

| | |
|------------------------|----------------------|
| Length overall | 26.8 m |
| Beam overall | 10.8 m |
| Depth at sides | 4.3 m |
| Draught | 2.1 m |
| Deadweight | 30.0 t |
| Cargo deck area | 80.0 m ² |
| Deck load | 1.5 t/m ² |
| Crew | 8 persons |
| (Industrial) personnel | 26 persons |

TANK CAPACITIES

| | |
|------------------------|---------------------|
| Fuel oil | 14.0 m ³ |
| Fuel trim | 16.0 m ³ |
| Fresh water | 3.5 m ³ |
| Sewage | 0.9 m ³ |
| Bilge water/ dirty oil | 0.4 m ³ |

PERFORMANCES

| | |
|---------------------|---------------|
| Speed | 25.0 kn |
| Range at max. speed | 600 - 1200 nm |

PROPULSION SYSTEM

| | |
|---------------|---------------------------------------|
| Main engines | 2x Caterpillar C32 TTA |
| Total Power | 2162 bkW |
| Gearboxes | 2x Reintjes "ZWVSA series (two speed) |
| Propulsion | 2x Fixed-pitch propellers |
| Bow Thrusters | 2x 64 kW, hydraulically driven |

ELECTRICAL EQUIPMENT

| | |
|----------------|-------------------------------|
| Network | 24V d.c., 400/230V 50 Hz a.c. |
| Generator sets | 2x 38.0 ekW-47.5 kVA |

DECK LAY-OUT

| | |
|---------------------|--|
| Anchor equipment | 1x 150 kg SHHP |
| Fendering | Rubber "D" type and heavy duty foam fender |
| Anchor winch | Electrically driven |
| Moon pool | |
| Foldable deck crane | Heila HLM 20-2S |

SHIP SYSTEMS

| | |
|-------------------------|---|
| General service pump | 2x electrically driven |
| Fuel trim system | 2x 2800 l/hr at 4 bar |
| Engine room ventilation | 8.000 m ³ /hr in each engine room |
| Fire extinguishing | Hand operated fire extinguishers, Fixed Fi-Fi system in engine room (Novec 1230) |
| Fuel cargo system | Connected to fuel trim system |

ACCOMMODATION

| | |
|------------------|---|
| Below main deck | 2x crew cabin, 2x harbour cabin |
| Main deck | 26 personnel seats, crew cabins, wet gear room, pantry, mess room and sanitary spaces |
| Bridge deck | Navigation console, small crew mess |
| Air conditioning | 112.000 BTU/hr |

NAUTICAL AND COMMUNICATION EQUIPMENT

| | |
|------------------------|-------------------------------------|
| Searchlight | 1x |
| Radar | 2x X-band |
| Electronic charts | Dual ECDIS system |
| DGPS | 1x |
| AIS | 1x |
| Compass | 1 x Magnetic, 1 x GPS |
| Autopilot | 1x |
| Echo sounder | 1x |
| Speed log | 1 x, Doppler log |
| Internal communication | Intercom and loudhailer CCTV system |
| External communication | GMDSSA2 |
| Weather system | 1x |

OPTIONAL

Satellite data communication

External communication GMDSS A3

Fleet broadband IV-SAT

Wi-fi system

